

EDGE LINEMARKER SPRAY

Safety Data Sheet

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Edge Linemarker Acrylic Spray Paint
 Container size 750ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Marker Paint

1.3. Details of the supplier of the safety data sheet

Supplier Brushware UK Ltd
 Rovex Business Park
 Hay Hall Road
 Tyseley
 Birmingham
 B11 2AQ

1.4. Emergency telephone number

Emergency telephone Brushware 0121 707 6677 Mon - Fri (9:00 - 16:00)

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229
 Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336 Asp. Tox. 1 - H304
 Environmental hazards Aquatic Chronic 3 - H412

2.2. Label Elements

Pictogram Aerosol 1 - H222, H229



Signal word Danger

Hazard Statements H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
Contains	ACETONE, BUTYL ACETATE -norm, SOLVENT NAPHTHA, LIGHT AROMATIC <0.1% BENZENE, 1,2,4-TRIMETHYLBENZENE, CUMENE, MESITYLENE

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Hazards Identification

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE			30-60%
CAS number: 68476-85-7	EC number: 270-704-2		
Classification Flam. Gas 1 - H220 Press. Gas (Liq.) - H280			
ACETONE			10-30%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			
SOLVENT NAPHTHA, LIGHT AROMATIC <0.1% BENZENE			5-10%
CAS number: 64742-95-6	EC number: 265-199-0	REACH registration number: 01-2119455851-35-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
BUTYL ACETATE -norm			5-10%
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336			

1,2,4-TRIMETHYLBENZENE			1-5%
CAS number: 95-63-6	EC number: 202-436-9	REACH registration number: 01-2119472135-42-XXXX	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
CUMENE			5-10%
CAS number: 98-82-8	EC number: 202-704-5	REACH registration number: 01-2119473983-24-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
MESITYLENE			5-10%
CAS number: 108-67-8	EC number: 203-604-4	REACH registration number: 01-2119463878-19-XXXX	
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments CAS 68476-85-7 - Petroleum Gas, The substance contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues. Never give anything by mouth to an unconscious person.
Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention immediately. Continue to rinse.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Vapours may cause drowsiness and dizziness.
Ingestion	Aspiration hazard if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor The following symptoms may occur: Nausea, headache, dizziness, coughing and breathing difficulty.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.
 Unsuitable extinguishing media Do not use a solid water stream.

5.2. Special hazards arising from the substance or mixture

Specific hazards Pressurised container: Must not be exposed to temperatures above 50°C. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
 Hazardous combustion products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Containers can burst violently or explode when heated, due to excessive pressure build-up. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved. Do not use water jet as an extinguisher, as this will spread the fire. Collect contaminated fire fighting water separately. Do not let enter the sewage system.
 Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure suitable respiratory protection is worn during removal of spillages in confined areas. For personal protection, see Section 8.
 For non-emergency personnel Keep upwind to avoid inhalation of gases, vapours, fumes and smoke.
 For emergency responders Wear anti-static protective clothing if there is a risk of ignition from static electricity. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Avoid inhalation of vapours.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at moderate temperatures in dry, well ventilated area. Keep away from heat, sparks and open flame. Pressurised container: Must not be exposed to temperatures above 50°C.

Storage class Extremely Flammable Aerosol

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters | Occupational Exposure Limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE	Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m ³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m ³
ACETONE	Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m ³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m ³
SOLVENT NAPHTHA, LIGHT AROMATIC <0.1% BENZENE	Long-term exposure limit (8-hour TWA): WEL 25 ppm 50 mg/m ³ (Sk)
BUTYL ACETATE -norm	Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m ³ Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m ³
CUMENE	Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk) 125 mg/m ³ (Sk) Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 250 mg/m ³ (Sk) WEL = Workplace Exposure Limit

ACETONE (CAS: 67-64-1)

DNEL Consumer - Oral; Long term : 62 mg/kg/day
Consumer - Dermal; Long term : 62 mg/kg/day
Industry - Dermal; Long term : 186 mg/kg/day
Consumer - Inhalation; Long term : 200 mg/m³
Industry - Inhalation; Short term : 2420 mg/m³
Industry - Inhalation; Long term : 1210

PNEC - Fresh water; 10.6 mg/l
- marine water; 1.06 mg/l
- Intermittent release; 21 mg/l
- Soil; 29.5 mg/l
- Sediment (Marinewater); 3.04 mg/kg
- Sediment (Freshwater); 30.4 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Personal protection

Wear protective work clothing.

Eye/face protection

The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Laminate >480 minutes. For users with sensitive skin, it is recommended that suitable protective gloves are worn.

Other skin and body protection

Provide eyewash station. Wear protective clothing. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Wear anti-static protective clothing if there is a risk of ignition from static electricity.

Hygiene measures

Wash promptly if skin becomes contaminated. Ensure the ventilation system is regularly maintained and tested. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn.

Thermal hazards

Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol
Colour	Various colours
Odour	Organic solvents
Odour threshold	No information available
pH	No information available
Melting point	No information available
Initial boiling point and range	No information available
Flash point	A flash point method is not available but the major hazardous component, the Propellant has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower
Evaporation rate	No information available
Evaporation factor	No information available
Flammability (solid, gas)	No information available
Upper/lower flammability or explosive limits	No information available
Other flammability	No information available
Vapour pressure	4.5 bar @ 20°C
Vapour density	No information available
Relative density	1.25-1.35 @ 20°C Density of paint base
Bulk density	No information available
Solubility(ies)	Partially soluble in water
Partition coefficient	No information available
Auto-ignition temperature	No specific test data are available
Decomposition temperature	No information available
Viscosity	No information available

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 717 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Highly volatile.
-----------	------------------

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	No known hazardous reactions if stored under normal conditions. Will not polymerise.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Strong acids. Strong alkalis. Strong oxidising agents.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation (ATE inhalation (vapours mg/l) 666,666.67)

General information	Contains organic solvents. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	The product contains organic solvents. Overexposure may depress the central nervous system, causing dizziness and intoxication.
Ingestion	Harmful: may cause lung damage if swallowed. Drowsiness, dizziness, disorientation, vertigo.
Skin contact	Repeated exposure may cause skin dryness or cracking. Contains components which may penetrate the skin.
Eye contact	Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting.
Acute and chronic health hazards	Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Arrhythmia (deviation from normal heart beat). Defatting, drying, and cracking of the skin.
Route of exposure	Inhalation. Skin absorption.
Target organs	Central nervous system. Respiratory system, lungs. Kidneys.
Medical symptoms	Narcotic effect. Vapours may cause drowsiness and dizziness.
Toxicological information on ingredients	

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Toxicological effects	Information given is based on data of the components and of similar products.
Acute toxicity - oral Notes (oral LD ₅₀)	Not applicable.
Acute toxicity - dermal Notes (dermal LD ₅₀)	Not applicable.
Acute toxicity - inhalation Notes (inhalation LC ₅₀)	LC ₅₀ >20 mg/l, Inhalation, Rat
Skin corrosion/irritation	Not irritating.
Serious eye damage/irritation	Not irritating.
Respiratory sensitisation	Not sensitising.
Skin sensitisation	Not sensitising.
Germ cell mutagenicity Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
Carcinogenicity	Carcinogenicity in humans is not expected.
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Does not contain any substances known to be toxic to reproduction.
Specific target organ toxicity - single exposure	A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
Specific target organ toxicity - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.
Inhalation	May cause respiratory system irritation.
Skin contact	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
Route of exposure	Inhalation Skin and/or eye contact

ACETONE

Toxicological effects	The toxicity of this substance has been assessed during REACH registration.
Acute toxicity - dermal Notes (dermal LD ₅₀)	2,000.0
Species	Rabbit
Skin sensitisation	Epidemiological studies have shown no evidence of skin sensitisation.
Skin contact	Irritating to skin.
Eye contact	Irritating to eyes.

BUTYL ACETATE -norm

Acute toxicity oral (LD ₅₀ mg/kg)	14,130.0
Species	Rabbit
Acute toxicity dermal (LD ₅₀ mg/kg)	17,600.0
Species	Rabbit
Acute toxicity inhalation (LC ₅₀ vapours mg/l)	29.2
Species	Rat
ATE inhalation (vapours mg/l)	29.2

1,2,4-TRIMETHYLBENZENE

Acute toxicity inhalation (LC ₅₀ vapours mg/l)	18,000.0
Species	Rat
ATE inhalation (vapours mg/l)	18,000.0

CUMENE

Serious eye damage/irritation	Eyes - rabbit- No irritation
-------------------------------	------------------------------

MESITYLENE

Acute toxicity inhalation (LC ₅₀ vapours mg/l)	24,000.0
Serious eye damage/irritation	Eyes - Rabbit - Mild eye irritation - 24hrs

SECTION 12: Ecological information

Ecotoxicity	The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Avoid the spillage or run off entering drains, sewers or watercourses.
-------------	---

Ecological information on ingredients.
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Ecotoxicity	Information given is based on data of the components and of similar products.
-------------	---

12.1. Toxicity | Ecological information on ingredients.
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Toxicity	Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.
----------	---

BUTYL ACETATE -norm

Acute toxicity - fish 96 hours: 100 mg/l, *Lepomis macrochirus* (Bluegill)
 Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 72 - 205 mg/l, *Daphnia magna*

1,2,4-TRIMETHYLBENZENE

Acute toxicity - fish LC50, 96 hours: 7.72 mg/l, *Pimephales promelas* (Fat-head Minnow)
 Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3.6 mg/l, *Daphnia magna*

CUMENE

Acute toxicity - fish LC50, 96 hours: 4.8 mg/l, *Oncorhynchus mykiss* (Rainbow trout)
 Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 2.14 mg/l, *Daphnia magna* OECD Test Guideline 202
 Acute toxicity - aquatic plants EC₅₀, 72 hours: 2.6 mg/l, Freshwater algae

MESITYLENE

Acute toxicity - fish LC50, 96 hours: 12.52 mg/l, *Carassius auratus* (Goldfish)
 Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 6 mg/l, *Daphnia magna*

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Ecological information on ingredients:
- PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Persistence and degradability The product is readily biodegradable.

- ACETONE

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

Ecological information on ingredients:
- PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Bioaccumulative potential Bioaccumulation is unlikely.

12.4. Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

Ecological information on ingredients:
- PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Not determined

Ecological information on ingredients:
- PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

- ACETONE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Do not puncture or incinerate, even when empty. Ensure containers are empty before discarding (explosion risk). Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Disposal methods	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	Empty Aerosol: 15 01 10 (Containing hazardous residues), Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 04 (No hazardous residues).

SECTION 14: Transport information

General	This product is packed in accordance with the Limited quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow the transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing they are labelled in accordance with the requirements of those regulations to show that they are transported as Limited Quantities. Aerosols not so packed must show the following.
---------	--

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	Aerosols
Proper shipping name (IMDG)	Aerosols
Proper shipping name (ICAO)	Aerosols
Proper shipping name (ADN)	Aerosols

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group (not applicable)

ADR/RID packing group	N/A
IMDG packing group	N/A
ICAO packing group	N/A

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant	No
--	----

14.6. Special precautions for user

IMDG Code segregation group	SG69
EmS	F-D, S-U
ADR transport category	2
Hazard Identification Number (ADR/RID)	Not applicable
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
--	-----------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	ECHA: Guidance on the Compilation of safety data sheets. (V3.1, November 2015)
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification procedures according to Regulation (EC) 1272/2008	Aerosol 1 - H222, H229: Weight of evidence. Eye Irrit. 2 - H319, STOT SE 3 - H336, Aquatic Chronic 3 - H412: Calculation method.	
Issued by	03/05/2017	
Revision date	ECHA: Guidance on the Compilation of safety data sheets. (V3.1, November 2015)	
Revision	8	
Supersedes date	01/08/2016	
SDS number	20581	
Hazard statements in full	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways.	H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.