

INSTABAND ECO®

Thermoplastic Overbanding Tape

ULTRA
CRETE

Ancillaries



Designed for the application to asphalt roads to prevent water ingress and progressive fretting.

- HAPAS Approved since 2012
- No waste, cut as required
- Prolongs the life of your repair
- Available in black and red
- Easy to use
- Fast installation
- Open to traffic: 10 minutes

Applications

UltraCrete Instaband ECO® is a thermoplastic, skid resistant overbanding and crack sealant tape designed for application to asphalt roads to prevent water ingress and progressive fretting, which leads to road structural failure.

Technical

Instaband ECO® is supplied in 5 metre rolls, 35mm wide (40mm wide when installed) x 3mm depth for easy handling. It has an anti-skid SRV of 60 and conforms to the requirements of S11.7 (SRV minimum 55) of the specification for the Reinstatement of Openings in Highways (SROH).

Preparation

Instaband ECO® is easy to apply on asphalt surfaces, always ensure that the area of application is clean, dry and free from dust, chemicals and any significant oil substances. If application to concrete is required the area should be primed. Please ensure that the area has completely cooled before the primer is applied.

Application

Preheat the surface making sure it is completely free from moisture. Remove Instaband ECO® from its protective wrapping and roll out on to the road surface, beaded side up. Once in place, heat the Instaband ECO with a propane torch. The heat should be applied from a distance of approximately 200-400mm (8"-16") from the material. Heat in a slow even sweeping motion making sure you do not spot-heat any area, as this may scorch the material causing discolouration. Instaband ECO® must be heated until the material starts to bubble and melt. Depending on air temperature, Instaband

ECO® will cool down and harden within 5-10 minutes of installation. When this has occurred, check for correct installation by trying to lift parts of the material at the edges using a knife or a chisel. If this can be lifted, simply reapply heat until adequate bonding has occurred.

Precautions

When the weather is warmer and the road temperature higher, the setting time for the material may be slightly longer. Do not use Instaband ECO® when it is raining or snowing. Ensure surfaces treated with salt or de-icers are fully washed as Instaband ECO® will not bond with these substances. Do not unpack more material than is necessary, as materials will harden when exposed to UV rays. Take care in excessively cold weather, as the material will become brittle.

Hot products only

Avoid skin contact with hot product. In case of contact with skin, immediately immerse in or flush area with water. Do not remove product from area and then seek medical advice. In case of contact with eyes rinse with plenty of water and seek medical assistance.

Storage

Do not expose to UV rays as materials will become hard. To ensure material does not become brittle prior to using on site, it is advisable to keep it in the footwell of a vehicle if possible. Store in closed original container in a dry and cool place, material must be handled with extra care in temperatures below 10°C as it will be less flexible.

Shelf life

Shelf life in correct conditions for sealed packaging is 12 months. In cold weather application will be assisted by storing tape overnight at room temperatures.

Health, Safety and Environmental

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash your hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste responsibly and in accordance with local authority requirements. A full material datasheet relating to this product is available from instarmac.co.uk

Quality assurance

All products are manufactured in a plant whose quality management system is certified / registered as being in conformity with BS EN ISO 9001. Our products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.

Technical data

Unit/packaging	5 metres x 35mm x 3mm roll, 12 rolls per box.
Colours	Black/ Red

Contact Us

Instarmac[®] Group plc, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom

Tel: +44 (0) 1827 254400 Fax: +44 (0) 1827 285386

Email: email@instarmac.co.uk Order: orders@instarmac.co.uk Website: instarmac.co.uk

Vers6.4.21 Uncontrolled if printed. For the most up-to-date version of this datasheet, please refer to this product's profile on our website which can be found at www.ultracrete.co.uk